

JM3-040A

J SERIES DC CROSSFLOW FAN



| | |
|----------------|--|
| VOLTAGE | 12V, 24V |
| BEARINGS | Ball Bearings |
| MOTOR | DC Brushless Type 3-phase |
| IMPELLER | Aluminum Alloy |
| LENGTH (C) | Min 13.8in (351mm), Max 17.8in (451mm) |
| AIRFLOW | 57~71 CFM (1.6~2.0m³/min) |
| OPERATING TEMP | 0°C~45°C |
| OPERATING LIFE | 30,000 hours @ 40°C |

| Model Number | | inches (mm) | | | V | A | RPM | Pressure (P) | | Airflow (Q) | | dBA | g |
|-----------------|---|-------------|-------|-------|----|------|------|--------------|--------------------|-------------|-----|-----|-----|
| | | A | B | C | | | | mmAq | inH ₂ O | m³/min | CFM | | |
| JM3-04030A12-3B | ① | 12.2 | 12.6 | 13.8 | 12 | 0.40 | 3250 | 1.4 | 0.06 | 1.6 | 57 | 42 | 455 |
| JM3-04030A24-3B | ① | (310) | (320) | (351) | 24 | 0.20 | | | | | | | |
| JM3-04035A12-3B | ② | 14.2 | 14.6 | 15.8 | 12 | 0.43 | 3100 | 1.3 | 0.05 | 1.9 | 67 | 40 | 500 |
| JM3-04035A24-3B | ② | (360) | (370) | (401) | 24 | 0.21 | | | | | | | |
| JM3-04040A12-3B | ③ | 16.1 | 16.5 | 17.8 | 12 | 0.46 | 3000 | 1.2 | 0.05 | 2.0 | 71 | 40 | 540 |
| JM3-04040A24-3B | ③ | (410) | (420) | (451) | 24 | 0.22 | | | | | | | |

