



## AX12B004-190 AX24B004-190

### BRUSHED DC AXIAL FAN SERIES STRAIGHT BLADE DESIGN

12V, 24V  
 324~359 CFM (550~610 m<sup>3</sup>/h)  
 Dual Ball Bearings  
 Housing: PA66 + 30% GF, UL94-V0  
 Impeller: PA66 + 30% GF, UL94-V0  
 Operating Temperature: -40°C ~ +70°C  
 Operating Life: 6,000 hours  
 IP55 Dust & Moisture Protection  
 RoHS

Model Number	Airflow Direction	Voltage (V)	Part Number	Current (A)	No. Speeds	Airflow (Q) (CFM) (m <sup>3</sup> /h)		CROSS REFERENCE PART NUMBER	
AX12B004-B190-1SP-02	Blowing	12	01.12.78B	≤ 4	1	324	550	SPAL	VA14-AP7 / C-34S
AX12B004-S190-1SP-02	Suction	12	01.12.68B	≤ 5	1	353	600	SPAL	VA14-AP7 / C-34A
AX24B004-B190-1SP-02	Blowing	24	01.24.78B	≤ 2	1	359	610	SPAL	VA14-BP7 / C-34S
AX24B004-S190-1SP-02	Suction	24	01.24.68B	≤ 3	1	359	610	SPAL	VA14-BP7 / C-34A

