



PTA12060-A

MINI BLOWER SERIES
HIGH SPEED-HIGH PRECISION

127 x 127 x 74mm

(4.98 x 4.98 x 2.91in)

12V, 24V

13.0~37.3 CFM (0.37~1.06 m³/min)

Ball Bearings

Lead Wires: UL1332 (+) Red; (-) Black, AWG 18

Operating Temperature: -40°C ~ +65°C

Operating Life: 10,000 hours @25°C

Tachometer (Frequency Generator)

PWM Speed Control

CE, RoHS

Model Number	Voltage (V)	Range (VDC)	Current (A)	Power (W)	Speed (RPM)	Airflow (Q) (CFM)	Airflow (Q) (m³/min)	Pressure (P) (inH ₂ O)	Pressure (P) (mmAq)	Noise (dBA)
PTA12060H12B-A	12	7~13.5	0.56	6.7	5000	13.0	0.368	2.25	57.1	57.1
PTA12060HH12B-A	12	7~13.5	5.00	60.0	11000	26.3	0.744	12.87	326.8	67.4
PTA12060HV12B-A	12	7~13.5	12.40	148.8	15000	37.3	1.056	29.61	752.0	71.9
PTA12060H24B-A	24	18~26.5	0.28	6.7	5000	13.0	0.368	2.25	57.1	57.1
PTA12060HH24B-A	24	18~26.5	2.5	60	11000	26.3	0.744	12.87	326.8	67.4
PTA12060HV24B-A	24	18~26.5	6.2	148.8	15000	37.3	1.056	29.61	752.0	71.9

