



# PTA8060-A

MINI BLOWER SERIES  
HIGH SPEED-HIGH PRECISION

80 x 77 x 60mm

(3.15 x 3.03 x 2.36in)

24V

18.4~33.8 CFM (0.52~0.96 m³/min)

Ball Bearings

Lead Wires: UL1332 (+) Red; (-) Black, AWG 18

Operating Temperature: -40°C ~ +65°C

Operating Life: 10,000 hours @25°C

Tachometer (Frequency Generator)

PWM Speed Control

CE, RoHS



Model Number	Voltage (V)	Range (VDC)	Current (A)	Power (W)	Speed (RPM)	Airflow (Q) (CFM)	Airflow (Q) (m³/min)	Pressure (P) (inH <sub>2</sub> O)	Pressure (P) (mmAq)	Noise (dBA)
PTA8060L24B-A	24	18~26.5	1.85	44.4	25000	18.40	0.515	19.6	498	68.4
PTA8060M24B-A	24	18~26.5	4.3	103.2	35000	25.40	0.719	39.7	1010	70.9
PTA8060M24B02-A	24	18~26.5	4.3	129.6	37000	28.10	0.795	44.1	1120	70.9
PTA8060H24B-A	24	18~26.5	8.5	204.0	44000	33.80	0.957	66.2	1681	84.3

