



PTA9725-B

MINI BLOWER SERIES
HIGH SPEED-HIGH PRECISION

97 x 130 x 73mm

(3.82 x 5.12 x 2.87in)

- 12V, 24V
- 19.7~31 CFM (0.56~0.88 m³/min)
- Ball Bearings
- Lead Wires: UL1007 (+) Red; (-) Black, AWG 22/24
- Operating Temperature: -40°C ~ +65°C
- Operating Life: 10,000 hours @25°C
- Tachometer (Frequency Generator)
- PWM Speed Control
- RoHS



Model Number	Voltage (V)	Range (VDC)	Current (A)	Power (W)	Speed (RPM)	Airflow (Q) (CFM)	Airflow (Q) (m ³ /min)	Pressure (P) (inH ₂ O)	Pressure (P) (mmAq)	Noise (dBA)
PTA9725H12B-B	12	7.5~13.5	0.60	7.2	9000	19.7	0.56	2.30	58.2	59.9
PTA9725LH12B-B	12	7.5~13.5	1.50	18.0	14000	30.9	0.88	6.03	153.2	68.6
PTA9725H24B-B	24	18~26.5	0.30	7.2	9000	19.7	0.56	2.30	58.2	59.9
PTA9725LH24B-B	24	18~26.5	0.75	18.0	14000	30.9	0.88	6.03	153.2	68.6

