

PTF-PZR SERIES

Roof-Mounted Exhaust Fans

PTF-PZR series Roof-Mounted Exhaust Fans are easy to install and maintain and are designed to provide high efficiency output with optimal airflow and pressure during operation.

Each fan is made of high-strength double insulation environmental material resulting in low energy consumption and low noise. It can operate from -20C to 60C and includes thermal protection and dual ball bearings for long-life operation up to 50,000 hours.

The fan cowl is made of high grade stainless steel that is UV and water resistant.

The two-speed motor can also be customized for three-speed or variable speed operation and the fans can also be customized with a timer, temperature sensor, humidity sensor, or other functions.

Protection Class: IP44



Model	Speed	Voltage/Freq (V/Hz)	Current (A)	Power (W)	Speed (RPM)	Airflow (CFM)	Airflow (m³/h)	Pressure (inH₂O)	Pressure (mmAq)	Pressure (Pa)	Noise (dBA)	Weight (kg)
PTF-200PZR	H	220~240V 50Hz	0.53	128	2450	494	840	1.41	35.81	352	63	5.1
	L		0.52	123	1950	406	690	1.10	27.94	274	55	
	H	100~120V 60Hz	1.47	162	2450	494	840	1.41	35.81	352	63	
	L		1.27	146	1950	406	690	1.10	27.94	274	55	

Dry air at 20°C and 760 mmHg
Performance data in accordance with
ISO 5801 and AMCA 210-99 Standards

HS: High Speed
LS: Low Speed

PTF-200PZR

